


Technical Data Sheet

BP Ultimate ULP 95



Description:

A top quality unleaded petrol meeting the requirements of both the OIPES, and SANS 1598:2006 specifications. BP unleaded has been formulated to include an exclusive additive package that enhances the characteristics of the petrol.

Application and Benefits:

BP unleaded can be used with confidence in most vehicles (>85%) on South African roads. All vehicles manufactured during 1995 or later are fully compatible, including those with catalytic converters. This fuel can be used inland or on the coast.

Main Benefits:

- **4X the cleaning power**, for a better performance
 - Latest generation detergent additive (Ultimate), ensuring cleaner intake systems
 - The cleaning power, **removing up to 75% of existing deposits**
 - Improved fuel economy of **up to 25km per full tank**
 - **Less damaging emissions**, making it more environmentally friendly
 - Gives your engine better performance with **up to 6.8% power improvement**
 - Does not contain any heavy metal additives that may adversely affect emission equipment.
-

Health, Safety and Environment:

Health, safety and environmental information are provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

BP or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local BP office.

Typical information from MSDS

Do not ingest. Never siphon by mouth. If ingested, do not induce vomiting. Avoid contact with skin and clothing. Wash thoroughly after handling. Avoid contact with eyes. Use only with adequate ventilation

STORAGE:

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress

Document name	Issue no.	Page	Issue Date	Revision Date	Document Owner
BPSA ULP 95		1 of 2	30 March 2009	February 2011	GFT SA



Technical Data Sheet

BP Ultimate ULP 95

SPECIFICATIONS:

Product meets both the OIPES and SANS 1598:2006 specifications.

TYPICAL PRODUCT DATA:

Property	Units	Test Method	SANS 1598	BP Typical
Distillation		ASTM D86		
Initial Boiling point	°C		Report	30
10% (v/v) recovery	°C		65 max	52
50% (v/v) recovery	°C		77 – 115	95
90% (v/v) recovery	°C		185 max	150
End Point	°C		215 max	210
Research Octane Number (RON)		ASTM D 2699	95min	95 min
Motor Octane Number (MON)		ASTM D 2700	85min	85 min
Copper strip corrosion (3h at 50°C)		ASTM D 130	1 max	1 max
Sulphur Content	%m/m	ASTM D 1266	0.05 max	0,05 max
Density at 20°C	kg/l	ASTM D 4052	0.710 – 0.785	0.7400
Lead	gPb/l	ASTM D 3116	0.013 max	< 1
Manganese	mg/L	ASTM D 3831	13 max	< 1
Colour		Visual	Green	Green
RVP	kPa	ASTM D323	45-75	58

For Further Information, Please Call
BPSA Global Fuels Technology @ +27-11- 488 5405/5431/5112

Document name	Issue no.	Page	Issue Date	Revision Date	Document Owner
BPSA ULP 95		2 of 2	30 March 2009	February 2011	GFT SA